

STRION® 2020 RECHARGEABLE FLASHLIGHT

DESCRIPTION: The Strion® 2020 features an easy-to-select mode switch positioned at the head of the light. 1,200 lumens, 28,000 candela, and a run time of 1 hour and 45 minutes on high are provided by the additional capacity of the 3450mAh battery. The Strion 2020 offers two independent on/off switches. The head switch, which includes a battery status indicator, and a tail switch.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in black.

DIMENSIONS: Length: 6.33 in (16.1 cm) Head Diameter: 1.25 in (3.18 cm)
Barrel Diameter: 0.95 in (2.41 cm) Diameter at Tri-Lobe Anti-Roll Flange: 1.35 in (3.43 cm)

WEIGHT: 5.7 oz (161.6 g) with battery (included in purchase)

LENS/OPTIC: High efficiency TIR optic for optimal light control. Optic impact and chemical resistant.

LIGHT SOURCE: High-power LED, white, impervious to shock with a 50,000-hour lifetime

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity.



ON/OFF/INTENSITY: Easily accessible push-button head switch and second push-button tail switch. Both switches offer full control independent of one another. One-handed operation of momentary, constant on, or strobe mode using either switch. Positioned in line with the head switch, the thumb-accessible, three-position slide switch allows for selection of high, medium, or low output. High intensity strobe activated by double click from any mode.

RUN TIME: See chart. All claims to 10% of initial lumen output. Strobe: 3.5 continuous hours.



BATTERY: Lithium-Ion with on-board safety control circuit, 3.6V, 3450mAh, rechargeable up to 1000 times.

CHARGING: Fits existing Strion® chargers.
Clamp style charge holder with digital control circuit that prevents overcharge.
The charger fully recharges battery in 4.5 hours and charges battery in product.
Charge base LED indication: LED Steady - Charging; LED Blinking - Charged.

FEATURES:



1,200 lumens with a high-power LED.
Mode selection switch.
Independent head and tail switches.
IPX7-rated design; waterproof to 1 meter.
2-meter impact resistance tested.
LED charge-continuity indicator on charger base.
Compact, snap-in charger mounts in any position.
Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS:   Meets applicable United Kingdom and European Community Directives
 CEC Compliant

OPTIONAL

ACCESSORIES: Safety wands, holster, flip lenses, Piggyback® charger, 6-unit bank charger

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		1,200 LUMENS	460 LUMENS	120 LUMENS
RUN TIME		1h 45min	5h 30min	12h
DISTANCE		335m	200m	110m
INTENSITY		28,000cd	10,000cd	3,000cd

